



USA



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated

31 August 2001

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

THIS PAGE BLANK (USPTO)

23 JAN 2001

THE PATENT OFFICE

A

23 JAN 2001

NEWPORT

23JAN01 E600150-2 002879
F01/7700 0.00-0101692.2

Request for grant of a patent

(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office
Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

PHGB010008

2. Patent application number

(The Patent Office will fill in this part)

0101692.2

3. Full name, address and postcode of the or of each applicant (underline all surnames)

KONINKLIJKE PHILIPS ELECTRONICS N.V.
GROENEWOUDSEWEG 1
5621 BA EINDHOVEN
THE NETHERLANDS

Patents ADP Number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

THE NETHERLANDS

074192914001

4. Title of the invention

MOBILE DEVICE COMPRISING A GPS RECEIVER

5. Name of your agent (if you have one)
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Andrew G. White
Philips Corporate Intellectual Property
Cross Oak Lane
Redhill
Surrey RH1 5HA

Patents ADP number (if you know it)

07655553001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority Application number
(if you know it)

Date of filing
(day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day/month/year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:

YES

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document.

Continuation sheets of this form

Description	8
Claims(s)	2
Abstract	1
Drawings	1

10. If you are also filing any of the following, state how many against each item:

Priority Documents

- Translations of priority documents
- Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)
- Request for preliminary examination and search (*Patents Form 9/77*)
- Request for substantive examination (*Patents Form 10/77*)
- Any other documents
(Please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

[Handwritten Signature]

Date 22-1-2001

12. Name and daytime telephone number of person to contact in the United Kingdom

01293 815339

(S. Townsend)

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered "Yes" *Patents Form 7/77* will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

DESCRIPTION

MOBILE DEVICE COMPRISING A GPS RECEIVER

5 This invention relates to a mobile device, including a mobile communications device such as a mobile telephone, comprising a GPS receiver and an alarm.

 It is well known to provide a GPS receiver in which replica GPS satellite
10 pseudorandom noise (PRN) code signals are continuously generated and correlated with received GPS signals in order to acquire them. Typically, as the replica codes are likely to have a different code phase to those of the received GPS signals and also a different frequency due to Doppler shift between the receiver and orbiting satellites, a two dimensional code frequency / phase
15 sweep is employed whereby such a sweep will eventually result in the incoming PRN code having the same frequency and code phase as that of the locally generated replica. If detected, the code is acquired and tracked, and the pseudorange information may be retrieved from which the position of the receiver may be calculated using conventional navigation algorithms.

20 It is further known to provide a mobile cellular telephone incorporating such a GPS receiver for the purpose of enabling operators of cellular telephone networks to determine the location from which a call is made and, in particular, for an emergency call to the emergency services. Of course for an emergency call, it is desirable for the call location to be available as soon as
25 possible, however, from a "cold start" where the GPS receiver does not have access to up to date ephemeris data or even worse from a "factory cold start" where the GPS receiver does not have an up to date almanac, the time to first fix (TTFF) can be anywhere between 30 seconds and 5 minutes.

 In order to reduce the TTFF, a GPS receiver may be provided with base
30 station assistance in order to acquire GPS signals more quickly. Such assistance may include the provision by the base station to the receiver of a precision carrier frequency reference signal for calibrating the local oscillator

used in the GPS receiver; the data message for up to date satellite almanac and ephemeris data from which Doppler shift for satellites in view can be determined; and the current PRN code phase. With such assistance, it is possible to sweep only a narrowed range of frequencies and code phases in which the target PRN code is known to occupy, thereby reducing the number of code instances that need to be checked and thus reducing the time for code acquisition. Base station assistance is further described in US patents 5841396 and 5874914 which are incorporated herein by reference.

A substantial reduction in the number of code instances that need to be checked enables an increase in the dwell time for each check without significantly affecting the overall time to acquisition. The benefit of this is that an increase in the dwell time increases the probability of acquiring weak GPS signals. For example, for a single code instance or dwell, correlation may occur over a period of 10ms, equivalent to approximately 10 PRN code repetitions (C/A mode), or over a longer period such as 100ms to 1s worth of individual 10ms correlation periods, incoherently summed as disclosed in US patent 5874914. The upshot of the above is that it is becoming more feasible to consistently acquire and track GPS signals in order to obtain a position fix with a mobile GPS receiver located indoors where signal reception is often very weak. This is very important as many telephone calls to the emergency services made on mobile telephones are made indoors.

US patent 5905460 to Odagiri et al. discloses a wrist watch comprising a GPS receiver and an alarm means which may take the form of a buzzer and is sounded in response to the watch being in a position where it can receive GPS signals (lines 31 to 33 of column 3) and when the GPS positioning calculations have been completed (lines 7 to 12 of column 3). It further disclosed in US patent 5905460 that the alarm is sounded after the following chain of events: the "wave" receiving condition is determined to be not good, then the wearer of the watch is determined to be walking, then the wave receiving operation is stopped and finally either a predetermined time or distance walked elapses (figures 11 and 12 with reference to line 117 of column 7 to line 17 of column 8). The purpose of such an alarm appears to be

to reduce power consumption of the wrist watch (line 64 of column 1 to line 11 of column 2).

It is an object of the present invention to aid the acquisition and tracking
5 of weak GPS signals such as those received indoors.

According to the present invention, there is provided a mobile device comprising a GPS receiver and an audible alarm configured to sound, during operation of the GPS receiver, in response to either adverse performance of
10 the GPS receiver or to an event which is adverse or likely to be adverse to the performance of the GPS receiver. For example, the alarm may sound in response to the inability of the GPS receiver to either acquire or track a GPS signal, or obtain or maintain a position fix

The alarm may also be configured to sound in response to movement of
15 the GPS receiver, including acceleration and higher order movement, in so far as that movement is adverse to the performance of the GPS receiver. For example, in order to measure the acceleration of the GPS receiver, it may comprise an accelerometer whereby the alarm is configured to sound in response to an output from the accelerometer.

20 In either case, it is the purpose of the alarm to draw the users attention to the fact that the GPS receiver is operating and that it is either suffering adverse performance or is subjected to an event, such as waving or shaking, which makes adverse performance more likely. It is expected that a user upon hearing the alarm would be reminded to hold the GPS receiver more still and /
25 or in a more prominent position in order to increase the chances of weak GPS signals being acquired and tracked, and a position determination being made accordingly.

For the avoidance of doubt, the above reference to the "operation of the GPS receiver" is intended to include attempted acquisition of the GPS signals
30 as well as signal tracking after acquisition, and if a digital GPS receiver is employed, sampling of the GPS signals.

Also provided in accordance with the present invention is a mobile device comprising a digital GPS receiver and an alarm configured to active at a predetermined time prior to sampling received GPS signals and yet further provided in accordance with the present invention is a mobile communications
5 device comprising a communications transmitter and receiver arranged for two-way communication with a base station, a GPS receiver and an alarm, including a visual or audible alarm, configured to activate in response to the device receiving a request transmitted from the base station for the device to return GPS pseudorange measurements or a position fix obtained using the
10 GPS receiver.

The present invention will now be described, by way of example only, of an embodiment of a mobile cellular telephone comprising a GPS receiver for use in a cellular telephone network with reference to the accompanying
15 drawing in which:

Figure 1 shows schematically a mobile cellular telephone MS1 in accordance with the present invention.

20 Figure 1 shows a mobile cellular telephone MS in accordance with the present invention, registered with a cellular telephone network base station BS and thereby facilitating voice and data communication between the telephone and a corresponding cellular telephone network (not shown) via that base station. Data communication is intended to include sending text messages (for
25 example using the short message service (SMS) protocol) and accessing the internet (for example using WAP or i-mode protocols). The mobile telephone comprises a communications transmitter (Tx) and receiver (Rx) 12 connected to a communications antenna 10 and controlled by a microprocessor (μ c) 13 for communication with the base station BS with which it is registered, a
30 speaker 15 and a display 16. As the design and manufacture of such telephones for two-way communication within a cellular telephone network are

well known, those parts which do not directly relate to the present invention will not be elaborated upon here further.

In addition to the conventional components of a mobile telephone, telephone MS, further comprises a GPS receiver (GPS Rx) 14 connected to a
5 GPS antenna 11 and controlled by the microprocessor 13. GPS signals may be sampled and stored (often referred to as taking a "snapshot"), and processed for the purpose of deriving pseudorange information from which the location of the mobile telephone can be determined using conventional navigation algorithms. Such methods for GPS signal acquisition, tracking and
10 position determination are well known, for example, GPS Principles and Applications (Editor, Kaplan) ISBN 0-89006-793-7 Artech House.

In addition to the conventional components of a cellular telephone network base station, base station BS further comprises a GPS antenna, receiver and microprocessor (not shown) which are in substantially continual
15 operation whereby the base station is in constant possession of up to date GPS satellite information. This information includes which of the orbiting satellites are presently in view (such satellites are likely to be common to both telephone and associated base station for even macrocells, obscuration aside); the GPS data message containing an up to date almanac and
20 ephemeris data, and the Doppler shift and current code phase of the GPS satellites signals as observed by the base station. As is known, in the event of the user of the mobile cellular telephone MS making an emergency call, the base station BS may provide this information to the telephone whereby it is then only required to sweep a narrowed range of frequencies and code phases
25 in which the target PRN code is known to occupy, ensuring rapid code acquisition and TTFF. This information is then transmitted back to the base station from the telephone, and then on to the emergency services operator, termed the Public Safety Answer Point (PSAP) in the US.

To aid acquisition and tracking of weak GPS signals and in accordance
30 with the present invention, the microprocessor 13 of the mobile cellular telephone MS is configured to sound an alarm using the speaker 15 during operation of the GPS receiver in response to either adverse performance of

the GPS receiver or to an event which is adverse or likely to be adverse to the performance of the GPS receiver. This includes the inability of the GPS receiver to do any of the following:

- acquire a GPS signal
- 5 • track a GPS signal
- obtain a position fix
- maintain a position fix

The telephone MS further comprises an accelerometer 17 able to output a signal to the microprocessor indicative of the acceleration to which the telephone is subjected to, for example, by the user waving and shaking the telephone. For any movement exceeding a predetermined threshold above which it is assumed that such movement adversely affects the performance of the GPS receiver, the microprocessor initiates the alarm.

As previously mentioned, the purpose of the alarm is to draw the users attention to the fact that the GPS receiver is operating and that it is either suffering or likely to suffer adverse performance attributable to perhaps waving or shaking the telephone. The audible alarm may be simple in nature, such as a buzzer, or more complicated and comprise pre-recorded verbal instructions to either reposition the mobile communications device, to refrain from moving the mobile communications device or to curb moving the mobile communications device. It may utilise a dedicated speaker or share the ear piece speaker or ringer present on conventional mobile telephones.

In alternative configurations of the above, the microprocessor may be configured to:

- 25 • activate an alarm in response to the telephone receiving a request transmitted from the base station for the device to return GPS pseudorange measurements or a position fix obtained using the GPS receiver.
- activate an alarm at a predetermined time prior to sampling received
- 30 GPS signals.

In either case, the alarm may be audible as described above or alternatively visual, comprising either textual or pictorial instructions, and

displayed on a display of the mobile communications device or as a separate light / indicator or a combination of any of these; and is again expected to remind a user to hold the GPS receiver more still and / or in a more prominent position in order to increase the chances of weak GPS signals.

5 With the former, the alarm may well be the first instance at which the user becomes aware that the GPS receiver is trying to operate, and hence of the importance to refrain from or at least to curb moving the telephone to aid signal acquisition and tracking. With the later, it is envisaged that the user upon notification by the alarm will at least temporarily hold the receiver still
10 such that a snapshot taken a short while later will be devoid of degradation causes by disruptive movement.

 The invention is described in relation to a GPS architecture employing a two dimensional code frequency / phase sweep, normally associated with early-minus-late correlation methods. However, fast convolution methods of
15 signal acquisition and, in particular, those involving Fast Fourier Transforms (FFTs), may be used in order to acquired the PRN codes. Such convolution methods are described in a paper entitled "FFT processing of direct sequence spreading codes using modern DSP microprocessors" by Robert G Davenport, IEEE 1991 National Aerospace and Electronics Conference NAECON 1991,
20 volume 1, pages 98 to 105, and also in US granted patent 5,663,734. The method of the present invention is equally is applicable such convolution methods.

 From a reading of the present disclosure, other modifications will be apparent to the skilled person skilled and may involve other features which are
25 already known in the design, manufacture and use of GPS receivers and component parts thereof and which may be used instead of or in addition to features already described herein. Although claims have been formulated in this application to particular combinations of features, it should be understood that the scope of the disclosure of the present application also includes any
30 novel feature or any novel combination of features disclosed herein either explicitly or implicitly, whether or not it relates to the same invention as presently claimed in any claim and whether or not it mitigates any or all of the

same problems as does the present invention. The applicants hereby give notice that new claims may be formulated to such features and/or combinations of such features during the prosecution of the present application or of any further application derived therefrom.

CLAIMS

1. A mobile device comprising a GPS receiver and an audible alarm configured to sound, during operation of the GPS receiver, in response to either adverse performance of the GPS receiver or to an event which is adverse or likely to be adverse to the performance of the GPS receiver.

2. A device according to claim 1 wherein the alarm is configured to sound in response to the inability of the GPS receiver to acquire or track a GPS signal.

3. A device according to claim 1 wherein the alarm is configured to sound in response to the inability of the GPS receiver to obtain or maintain a position fix.

4. A device according to claim 1 wherein the alarm is configured to sound in response to movement of the GPS receiver in so far as that movement is adverse to the performance of the GPS receiver.

5. A device according to claim 4 wherein the alarm is configured to sound in response to acceleration of the GPS receiver.

6. A device according to claim 5 wherein the GPS receiver further comprises an accelerometer to measure the acceleration of the GPS receiver whereby the alarm is configured to sound in response to an output from the accelerometer.

7. A device according to any of the preceding claims wherein the audible alarm comprising pre-recorded verbal instructions to either reposition the mobile communications device, to refrain from moving the mobile communications device or to curb moving the mobile communications device.

8. A mobile device comprising a digital GPS receiver and an alarm configured to activate at a predetermined time prior to sampling received GPS signals.

5 9. A mobile communications device comprising a communications transmitter and receiver arranged for two-way communication with a base station, a GPS receiver and an alarm configured to activate in response to the device receiving a request transmitted from the base station for the device to return GPS pseudorange measurements or a position fix obtained using the
10 GPS receiver.

10. A device according to claim 8 or claim 9 wherein the alarm is an audible alarm.

15 11. A device according to claim 10 wherein the audible alarm comprising pre-recorded verbal instructions to either reposition the mobile communications device, to refrain from moving the mobile communications device or to curb moving the mobile communications device.

20 12. A device according to claim 8 or claim 9 further comprising a display wherein the alarm is a visual alarm displayed on the display.

25 13. A device according to claim 12 wherein the visual alarm comprises instructions to either reposition the mobile communications device, to refrain from moving the mobile communications device or to curb moving the mobile communications device.

ABSTRACT

MOBILE DEVICE COMPRISING A GPS RECEIVER

5 A mobile device (MS) is disclosed comprising a GPS receiver (14) and
an audible alarm (13, 15) configured to sound, during operation of the GPS
receiver, in response to either adverse performance of the GPS receiver or to
an event which is adverse or likely to be adverse to the performance of the
GPS receiver. The alarm may sound in response to the inability of the GPS
10 receiver to either acquire or track a GPS signal, or obtain or maintain a
position fix. Also, the alarm may sound in response to movement of the GPS
receiver, including acceleration and higher order movement of the GPS
receiver, in so far as that movement is adverse to the performance of the GPS
receiver.

15

[figure 1]

THIS PAGE BLANK (USPTO)

1/1




Fig. 1

THIS PAGE BLANK (USPTO)